

MATERIAL SAFETY DATA SHEET

03/03/08

PAGE 1

-----SECTION 01-----

MANUFACTURED FOR: GEMINI COATINGS, INC.
2300 HOLLOWAY DRIVE
EL RENO, OK 73036
800-262-5710

"X" INDICATES SUBSTANCE IS A HAP. REPORTABLE UNDER SARA III, SECTION 313, IF 10,000 LBS OF AN ITEM USED PER CALENDAR YEAR.
DENSITY, % SOLIDS AND % VOC ANALYSIS REFERENCES METHOD 24.

TRADE NAME : WB-1410
FORMULA : 10° WHITE MODIFIED URETHANE
HMIS NUMBER : 1 0 0 1

-----SECTION 02 – HAZARDOUS INGREDIENTS-----

<u>INGREDIENT DESCRIPTION</u>	<u>% BY WGT.</u>	<u>C.A.S. NO.</u>	<u>P.E.L.</u>	<u>T.L.V.</u>
2 BUTOXYETHANOL	2.53	111-76-2	50.00	20PPM

-----SECTION 03 – PHYSICAL DATA-----

BOILING POINT : 180 % SOLIDS (+2)/WGT 47.759
VAPOR PRESSURE : 54.00 % SOLIDS (+2)/VOL 32.546
VAPOR DENSITY : 4.60 VOC (LB/GL) AS SUPPLIED: .445
WATER SOLUBLE : Y VOC IS LESS ANY FEDERALLY EXEMPT SOLVENT.
SPEC GRAVITY : 1.250
% VOLATILE/VOL : 67.454 SQ.FT. COVERAGE (1 MIL): 522

-----SECTION 04 – FIRE AND EXPLOSION HAZARD DATA-----

FLASH POINT : OVER 200 TCC N/R
LEL : N/A
UEL : N/A

EXTINGUISHING MEDIA: Foam, CO2, dry chemical, water fog.
UNUSAL FIRE AND EXPLOSION HAZARDS: The material will not support combustion unless the water has evaporated.
SPECIAL FIREFIGHTING PROCEDURES: Water may be used to cool closed containers, to prevent pressure build-up.
UNUSAL FIRE AND EXPLOSION HAZARDS: Container may burn or leak in heat of fire.

-----SECTION 05 – HEALTH HAZARD DATA-----

TLV : Approx. 20 ppm
EFFECTS OF EXCESSIVE OVEREXPOSURE: Intentionally and deliberately concentrating and inhaling the contents may be harmful. Wear an appropriate, properly fitted respirator (NIOSH/MSHA APPROVED)

MATERIAL SAFETY DATA SHEET

before and during application unless air monitoring demonstrates vapor/mist levels are below applicable limits. This product may cause eye, skin and respiratory tract irritation.

FIRST AID : Eye Contact : Flush with lukewarm water for at least 15 minutes.

Consult physician

Skin Contact : Wash affected areas with water.

Inhalation : Remove exposed individual to fresh air. Consult physician.

Ingestion : Rinse mouth immediately. Give exposed individual 6 – 9 oz. of liquid. Consult physician.

Substances have not been identified as a carcinogen or a probable carcinogen by NTP, IARC OR OSHA.

-----SECTION 06 – REACTIVITY DATA-----

STABILITY: Stable

HAZARDOUS DECOMPOSITION PRODUCTS: When exposed to fire, produces normal products of combustion.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS POLYMERIZATION CONDITIONS TO AVOID: None known.

-----SECTION 07 – SPILL OR LEAK PROCEDURES-----

STEPS TO BE TAKEN INCASE MATERIAL IS RELEASED OR SPILLED: Remove with inert absorbent. Sweep or scrape up and containerize. Rinse affected area thoroughly with water.

WASTE DISPOSAL METHOD: Observe all applicable Federal/State regulations and local ordinances.

-----SECTION 08 – SPECIAL PROTECTION INFORMATION-----

-----SECTION 09 – SPECIAL PRECAUTIONS-----

PRECAUTIONS TO BE TAKEN: KEEP FROM FREEZING.

Protect drums against physical damage. Do not take internally. Wash hands thoroughly after handling.

THE INFORMATION CONTAINED HEREIN IS INFORMATION RECEIVED FROM OUR RAW MATERIAL SUPPLIERS AND OTHER SOURCES AND HIS BELIEVED TO BE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY REPRESENTATION OR WARRANTY, EXPRESSED OR IMPLIED, REGARDING ITS ACCURACY OR COMPLETENESS. THE CONDITIONS OF HANDLING, STORAGE USE AND DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME ANY RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLINE, STORAGE, USE OR DISPOSAL OF THE PRODUCT.