



PRODUCT DATA SHEET

Sanding Sealer

L131 Sanding Sealer

DESCRIPTION	CHARACTERISTICS	SPECIFICATIONS
<p>This product was formulated for either airless or conventional spray application so that it is not necessary to thin the product with expensive thinners thus, a high build, high quality finish is achieved in fewer coats than most lacquer systems. When applied with heated spray equipment, the contractor will obtain a finish comparable, in appearance, to high quality furniture finishes. The highest quality, cost competitive raw materials are used in producing this series of lacquer. DO NOT use as a water clear finish over light substrates, these products have a natural, mild amber cast. For a water clear finish see the 160 series.</p> <p>Product Advantages:</p> <ul style="list-style-type: none"> ➤ AIM Compliant ➤ High Solids ➤ Spray Viscosity Without Adding Thinners ➤ High Quality ➤ Cost Competitive 	<p>Viscosity: 14' #3 Zahn</p> <p>Weight Solids: 27%</p> <p>Volume Solids: 21%</p> <p>Weight/Gallon: 7.72</p> <p>Film Hardness: B-HB Overnight</p> <p>Color: 2-3</p> <p>VOC (Reg/coating): 5.63 lb/gal or 674 g/l</p> <p>VOC (Act./material): 5.63 lb/gal or 674 g/l</p> <p>HAPs: 1.50</p> <p>Coverage: 339 sq. ft. per gallon at one mil dry film thickness</p> <p>Dry Time: Dust free in 8 minutes, light sand in 20 minutes, recoat in 45 minutes, may be forced dried up to 120°. Relative humidity will affect the speed of drying. Ideal conditions are 75° or warmer at 30-40% relative humidity, or less. Dry time will be faster at higher temperatures and lower humidities, and equally slower at colder temperatures and higher humidities.</p> <p>Shelf Life: 12 months if unopened and stored in a cool dry area. Always rotate stock.</p> <p><i>Note: These numbers represent actual control values on a smooth, sanded substrate. Spray techniques, texture, and sealing as well as film thickness may give different results on actual work, but they may be used for comparison. To the best of our knowledge, the above technical data is true and accurate at the date of issuance but is subject to change without prior notice.</i></p>	<p>Surface Preparation: New wood: Remove any dirt, grease, glue or other contaminants and sand wood as required. Moisture content of wood should be 7-9%. Old wood: Strip old finishes completely and remove all contaminants from the surface. Make sure the surface is dry, sand as required. Finish as new work.</p> <p>Material Preparation: High Solids Lacquers are ready to use as packaged. Mix or agitate thoroughly before use. Thinning is not recommended for airless application. Blush Retarder, L61, may be added in small amounts at levels not to exceed 5% by volume if necessary in humid weather to prevent "blushing".</p> <p>Application: Because of the short dry time, this sealer must be applied with professional spray equipment. We recommend a coating system composed of one coat of sealer and two coats of topcoat at 4-5 wet mils per coat. The temperature of the product will affect viscosity. All products are formulated to achieve the highest possible solids content that will allow proper spray atomization without the addition of costly chemical solvents. We do not recommend that the sealer be sprayed hot; however, all finish coat products can be sprayed hot with excellent results.</p> <p>Clean Up: Use #500 Lacquer Thinner to clean up all equipment. Dispose of in accordance with Federal, State, and Local regulation regarding pollution.</p>

The following supersedes any provision contained in the forms, letters and papers of your company. This product is designed and intended for professional application only. All products should be thoroughly tested under application conditions prior to use. The information contained herein is believed to be reliable. **HOWEVER, GEMINI MAKES NO WARRANTY CONCERNING THIS PRODUCT, WHETHER EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** UNDER NO CIRCUMSTANCES SHALL GEMINI BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR ANY OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH OF WARRANTY, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY, ARISING OUT OF THE USE OR HANDLING OF THIS PRODUCT. THE SOLE REMEDY OF THE BUYER AND THE SOLE LIABILITY OF GEMINI FOR ANY CLAIMS SHALL BE LIMITED TO THE BUYER'S PURCHASE PRICE OF THE PRODUCT WHICH IS THE SUBJECT OF THE CLAIM OR THE AMOUNT ACTUALLY PAID FOR SUCH PRODUCT, WHICHEVER IS LESS. TECHNICAL ADVICE FURNISHED BY GEMINI SHALL NOT CONSTITUTE AN EXPRESS WARRANTY, WHICH IS EXPRESSLY DISCLAIMED. ALL TECHNICAL ADVICE GIVEN IS ACCEPTED AT THE RISK OF THE BUYER.

CAUTION: DANGER! FLAMMABLE! VAPORS MAY CAUSE FLASH FIRE. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. INJURIOUS TO EYES. KEEP OUT OF THE REACH OF CHILDREN! BEFORE using this product it is essential that the "Material Safety Data Sheet" describing the product as well as the "Product Label" be reviewed. If your company does not have such information or has any questions, contact the manufacturer.

Date: Feb 07